

OFFER NO. :	03/02/2016	DATE OF DOC. :	03/02/16
	214/2016 POS. 1		
PRODUCT CODE :	P33506200100398		
D.C. MOTOR TYPE:	NP 80NM 2 - 06 PVA/2001		
QUANTITY :	1	DELIVERY TIME:	0
BUYER :	IMPEXRON GMBH		



SC/MR

**ELECTRICAL DATA**

POWER (KW) :1,89/  
 ARM. VOLT. (V) :260,00/  
 SPEED (RPM) :1628/  
 ARM. CURR. (A) :9,30/  
 FIELD CURR(A) : 1,30/  
 NO. OF POLES : 2

DUTY : S1  
 SUPPLY : S.F.C.B.  
 ECCITAZ. : SEPARATE WITHOUT STAB.SERIES

INS. CLASS : H DT H  
 FIELD VOLT(V): 170,00/0,00

**MECHANICAL DATA**

ENVIRONMENT : NORMAL ENVIRONMENT  
 MOUNTING (IM) : 2001 B35  
 PROTECTION (IP) : 23 S  
 FAN SUPPLY : 230/400V +/- 10% 50HZ THREEPHASE  
 DIRECT COUPLING  
 VIBRATION GRADE : N  
 SHAFT MATERIAL : STANDARD  
 D.E. SHAFT : SPECIAL DIAM. (MM) : 19 j6  
 D.E BEARING : BALL

ALTITUDE (MT.) : 1000  
 FLANGE : STANDARD  
 COOLING (IC) : 06 PVA

TROPICALISATION

LENGTH (MM) : 40 WITH KEY

COOLER MOUNTING : TOP  
 TERMINAL BOX : STANDARD - TOP

PAINTING : STANDARD - CYCLE N. 1  
 RAL : 6011

**INCORPORATED ACCESSORIES**

THERMAL PROTECTION: 1-KLIXON ON AUXILIARY POLE  
 FILTER

**ACCESS. PROVISIONS**

PROVISION FOR TACHO/ENCODER: WITH COUPLING  
 TACHOG./ENCODER : REO 444N1-60 V/ 1000 RPM D11

- PROVISION ONLY -

**GENERAL DATA**

REFERENCE TEMP. : 40 C.  
 D.E. BEARING : 6305-2Z/C3  
 TOTAL WEIGHT (KG) : 40,00  
 DYNAMIC LOAD OF SHORT CIRCUIT (KG) :90  
 PACKING : ON PALLET

ELECTRIC STANDARDS. : CEI,IEC  
 NAMEPLATE : GERMAN  
 NDE BEARING : 6204-2Z/C3  
 MOMENT OF INERTIA J (KGM2) :0,0140