

HIGH PRESSURE COIL



In accordance with DIN 477/ 230 bar, with hexagon nut, coil tube \varnothing 6 mm. Material SS/ PCTFE. Outlet, swivel nut M14 \times 14.5 or NPT 1/4"m. Pigtail tubing allows for connection of the gas panel with gas supply in a limited spatial area. Built-in handles guarantee a zero potential and gas-tight connections. Cylinder connections also in accordance with other norms such as AFNOR, NEN, ... or 300 bar cylinder on request.

Art.-Nr. M14 \times 1.5f	Art.-Nr. NPT1/4"m	DIN connection
H27415664	H27448064	FA 1
H27415764	H27433264	FA 5
H27415864	H27427364	FA 6
H27416944	H27462464	FA 7
H27415964	H27446364	FA 8
H27416064	H27433464	FA 9
H27414564	H27433564	FA 10
H27416164	H27433664	FA 11
H27416264	H27433764	FA 13
H27416364	H27433864	FA 14

SPIRAL COIL



In accordance with DIN 477/ 230 bar, tube \varnothing 1/8", with hex nut , outlet NPT 1/4"m. material SS/PCTFE. Cylinder connections also in accordance with other norms such as AFNOR, NEN, ... upon request.

Art.-Nr.	DIN Connection
H27430564	FA 1
H27430664	FA 5
H27430764	FA 6
H27431064	FA 9
H27431164	FA 10
H27431264	FA 11
H27432264	FA 13
H27431364	FA 14