



Ordering details

Voltage	h	Type	Auxiliary contact	Cable entries	Weight approx.	Order No.
Type 16 A 3-pole						
200-250 V		Wall socket	–	M25 KU	1.2 kg	GHG 511 4306 R0001
		Wall socket	–	M20 GE	1.2 kg	GHG 511 4306 R0002
		Wall socket	–	M20 ME	1.3 kg	GHG 511 4306 R3001
	6	Wall socket	–	M20 GM	1.3 kg	GHG 511 4306 R3003
		Flange socket			0.4 kg	GHG 511 8306 R0001
		Coupler			0.7 kg	GHG 511 3306 R0001
		Plug			0.35 kg	GHG 511 7306 R0001
Type 16 A 4-pole						
200-250 V		Wall socket	–	M25 KU	1.8 kg	GHG 511 4409 R0001
		Wall socket	–	M20 ME	1.9 kg	GHG 511 4409 R3001
		Flange socket			1.0 kg	GHG 511 8409 R0001
	9	Coupler			1.7 kg	GHG 511 3409 R0001
		Plug			0.7 kg	GHG 511 7409 R0001
380-415 V		Wall socket	–	M25 KU	1.8 kg	GHG 511 4406 R0001
		Wall socket	–	M20 ME	1.9 kg	GHG 511 4406 R3001
		Wall socket	yes	M25 KH	1.8 kg	GHG 511 4406 R0501
	6	Flange socket			1.0 kg	GHG 511 8406 R0001
		Coupler			1.7 kg	GHG 511 3406 R0001
		Plug			0.7 kg	GHG 511 7406 R0001
480-500 V		Wall socket	–	M25 KU	1.8 kg	GHG 511 4407 R0001
		Wall socket	–	M20 ME	1.9 kg	GHG 511 4407 R3001
		Wall socket	yes	M25 KH	1.8 kg	GHG 511 4407 R0501
	7	Flange socket			1.0 kg	GHG 511 8407 R0001
		Coupler			1.7 kg	GHG 511 3407 R0001
		Plug			0.7 kg	GHG 511 7407 R0001
600-690 V		Wall socket	–	M25 KU	1.8 kg	GHG 511 4405 R0001
		Wall socket	–	M20 ME	1.9 kg	GHG 511 4405 R3001
		Wall socket	yes	M25 KH	1.8 kg	GHG 511 4405 R0501
	5	Flange socket			1.0 kg	GHG 511 8405 R0001
		Coupler			1.7 kg	GHG 511 3405 R0001
		Plug			0.7 kg	GHG 511 7405 R0001
Type 16 A 5-pole						
200-250 V		Wall socket	–	M25 KU	1.8 kg	GHG 511 4506 R0001
380-415 V		Wall socket	–	M20 ME	1.9 kg	GHG 511 4506 R3001
		Wall socket	yes	M25 KH	1.8 kg	GHG 511 4506 R0501
		Flange socket			1.0 kg	GHG 511 8506 R0001
		Coupler			1.7 kg	GHG 511 3506 R0001
6	Plug			0.7 kg	GHG 511 7506 R0001	

Other voltage ranges and versions available on request.

KU = 1 x plastic cable glands M25 for Ø 8 -17 mm, 1 x M25 Ex-screw plug plastic

KH = 2 x plastic cable glands M25 for Ø 8 - 17 mm, auxiliary contact, 1 NO

ME = 2 x metal thread M20 with Ex-screw plug plastic

GE = 2 x plastic thread M20 without cable gland/screw plug

GM = 2 x metal thread M20 without cable gland/screw plug