



Ready-to-use friction-locked shaft-hub connection. For motor shafts in accordance with DIN 748 with a k/6/m6 tolerance zone.

- [Examples](#)
- [Benefits](#)
- [Function](#)
- [Transmittable Forces](#)

Order No. click for request	Name CAD-Download	Diameter in mm			Clamping screw				Transmittable forces	
		d ₁	d ₂	L	ISO 4762	h	M _A	No.	M	F _a
			h5			mm	Nm		Nm	N
K-11301401	DSM 14.2	14	26	26	M3	3	2	4	50	7100
K-11301602	DSM 16.1	16	32	26	M4	4	5	6	95	11900
K-11301603	DSM 16.2	16	32	36	M4	4	5	6	130	16300
K-11301601	DSM 16.28	16	28	26	M3	3	2	6	66	8250
K-11301802	DSM 18.2	18	34	36	M4	4	5	6	160	17800
K-11301801	DSM 18.30	18	30	26	M3	3	2	6	92	10222
K-11301902	DSM 19.1	19	35	26	M4	4	5	6	130	13700
K-11301903	DSM 19.2	19	35	36	M4	4	5	6	200	21100
K-11301901	DSM 19.32	19	32	26	M3	3	2	6	100	10526
K-11302002	DSM 20.1	20	40	36	M5	5	10	5	190	19000
K-11302003	DSM 20.2	20	40	46	M5	5	10	5	240	24000
K-11302001	DSM 20.32	20	32	26	M3	3	2	6	108	10800
K-11302202	DSM 22.1	22	42	36	M5	5	10	5	220	20000
K-11302203	DSM 22.2	22	42	46	M5	5	10	5	290	26400
K-11302201	DSM 22.35	22	35	26	M3	3	2	6	122	11091
K-11302402	DSM 24.1	24	44	36	M5	5	10	5	260	21700
K-11302403	DSM 24.2	24	44	46	M5	5	10	5	360	30000
K-11302401	DSM 24.36	24	36	26	M3	3	2	6	145	12083
K-11302502	DSM 25.1	25	45	41	M5	5	10	6	280	22400
K-11302503	DSM 25.2	25	45	52	M5	5	10	6	450	35900
K-11302501	DSM 25.37	25	37	26	M3	3	2	6	184	14720
K-11302802	DSM 28.1	28	48	41	M5	5	10	6	320	22900
K-11302803	DSM 28.2	28	48	52	M5	5	10	6	550	39300
K-11302801	DSM 28.40	28	40	26	M3	3	2	6	205	14643
K-11303002	DSM 30.1	30	52	57	M6	6	17	5	690	46000
K-11303003	DSM 30.2	30	52	62	M6	6	17	5	710	47300
K-11303001	DSM 30.42	30	42	26	M3	3	2	6	220	14667
K-11303202	DSM 32.1	32	55	57	M6	6	17	5	770	48100
K-11303203	DSM 32.2	32	55	62	M6	6	17	5	800	50000